

MC 521 YELLOW LABEL SETUP FOR DUAL LOW ENERGY

Power **ON**

Turn Mode selector switch to **CLOSED** or **OFF**

Remember when releasing enter you only have 2 seconds to make a change

A) Hold enter and press down to #99

Release enter, press down one time to #00

B) Hold enter and press down to #96

Release enter, press up one time to #01

You will then see "A0" on display

C) Hold enter and press up to #00

Release enter, press up to until you see #08

You will then see "AO" on display

D) Hold enter and press up to #01 (motor 01)

Release enter, go to "00" for right hand or "01" for left hand

You will then see "A0" on display

E) Hold enter and press up to #02 (motor 02)

Release enter, go to "00" for right hand or "01" for left hand

You will then see "A0" on display

F) Hold enter and press up to #03

Release enter, press **UP** one time

You will see "20" briefly, then "A1" on display

G) Hold enter and press up to #11

As long as you don't have sentrex, release enter and change it to #00

You will see "A1" on display

H) With the doors in the fully closed position, you will now flip your mode switch to HOLD OPEN. AS SOON AS THE DOOR BEGINS TO MOVE, FLIP THE MODE SWITCH BACK TO CLOSED/OFF. The door will now go thru a "learn" process. This consists of the door opening and closing several times until you see "A2" on the display. Once "A2" is present you will:

I) Hold enter and press down to #99

Release enter, press up one time to "01"

It will then read "20" briefly, then go to "00"

At this point you may put your switch to **AUTOMATIC** and run your door.