

MC 521 **BLACK LABEL PRO** SETUP FOR **DURA GLIDE SLIDING** PACKAGE

Power **ON**

Turn Mode selector switch to **CLOSED** or **OFF**

*****Remember when releasing enter you only have 2 seconds to make a change*****

A) Hold enter and press down to **#99**

Release enter, press down one time to **#00**

B) Hold enter and press down to **#96**

Release enter, press up one time to **#01**

You will then see "A0" on display

C) Hold enter and press up to **#00**

Release enter, press up to until you see **#01**(single motor) or **#02**(dual motor)

You will then see "AO" on display

D) Hold enter and press up to **#01**

Release enter, go to "**00**" for right hand(CCW*) or "**01**" for left hand(CW**)

*when manually opening door, pulley on gearbox spins Counter Clockwise

**when manually opening door, pulley on gearbox spins Clockwise

You will then see "A0" on display

E) Hold enter and press up to **#03**

Release enter, press **UP** one time

You will see "20" briefly, then "A1" on display

F) Hold enter and press up to **#11**

Release enter, go to "**00**" for Rotary switch logic, or "**01**" for Rocker switch logic

You will see "A1" on display

➔ If you have an Electric lock you will do this next step(G), if **NO** electric lock is present, please skip (G).

G) Hold enter and press up to **#07**

Release enter, change to "**00**" for Fail Safe lock, or "**01**" for Fail Secure lock.

H) Are you using Stanley Pro Safety Beams wired in to TB6? If so, hold enter and go to **#20**

Release enter and make sure it is set to "**01**"

IF NOT using Pro safety beams in TB6: Hold enter and press up to **#20**

Release enter and hit down one time to change the display to "**00**"

I) Are you using Monitored Sensors? If so, hold down enter and go to "**19**"

Release enter and make sure it is set to "**02**"

IF NOT using Monitored Sensors, hold down enter and go to "**19**"

Release enter and make sure it is set to "**04**"

J) With the door in the fully closed position, you will now flip your mode switch to **HOLD OPEN**. **AS SOON AS THE DOOR BEGINS TO MOVE, FLIP THE MODE SWITCH BACK TO CLOSED/OFF**. The door will now go thru a “learn” process. This consists of the door opening and closing one time until you see “A2” on the display. Once “A2” is present you will:

K) Hold enter and press down to **#99**

Release enter, press up one time to **“01”**

It will then read **“20”** briefly, then go to **“00”**

At this point you may put your switch to **AUTOMATIC** and run your door.

Need additional help? Contact us at 1-800-222-9601 for Tech Support!